
Allumio Lighting Design

Apollo Series

Allumio

Outdoor

Apollo Series



The Apollo Series is an evolution in bollard lighting in both technology and design, producing an elegant fitting that integrates well in all environments to provide a modern and sleek look.

We have developed a new innovative optic system guaranteeing visual comfort, with excellent horizontal effect while completely hiding the light source from view. All while still producing outstanding uniformity at ground level.

The uniformity produced by the Apollo range has allowed this fitting to illuminate the horizontal plane without the base of the fitting creating shadow to provide perfectly patterned light from the closest point to the farthest point from the pole.

Standard Bollard Fitting

Apollo Bollard Series





Apollo Series

The Apollo Asymmetical bollards with a height of 900mm will provide uniformed path lighting at a spacing of 7 metres.



180° Asymmetric H=900mm







The Apollo Symmetical bollards with a height of 900mm will provide uniformed path lighting at a spacing of 8 metres.

The Apollo Bollard is fixed to the ground with a fixing base made of die –cast alluminium alloy with low copper content to provide resistance to corrosion.



360° Symmetric H=900mm







Apollo Series

- · Its sleek design with invisible light source provides a superior visual comfort and is glare free, while incorporating extreme strength and resistance with its IK10 rating to vandalism.
 - **CRI>83**
 - UGR<19
 - 3 Step MacAdam Ellipse
- Heights 280mm, 600mm, 900mm
- Diameter (mm) 180
- Working Temperature -20 ~ 50°C
- IP66
- IK10
- Graphite Grey frame standard, other colours available on request
- 5 year warranty
- The external Aluminium parts undergo a multi-step pre-treatment, utilizing premium ultra-weatherable polyester powder coating to withstand extended outdoor exposure, providing excellent resistance to corrosion, atmospheric agents and UV rays, degradation and abrasion.















Allumio



ALLUMIO APOLLO SERIES

| Height (mm) | 280 | 600 900 | |
|------------------|---------------------------|----------------------------|----------------------------|
| Wattage | 6 | 15 | 15 |
| Options | 10 | 20 | 24 |
| (w) | 12 | 30 | 36 |
| Lumen Outputs | 830lm 1380lm 1850lm | 2300lm 3000lm 4360lm | 2300lm 3550lm 5030lm |
| ССТ | 3000k | 4000k | 5000k |
| | (3) | (4) | (5) |
| Control | Switching | 0-10v Dimming | Dali Dimming |
| Options | (S) | (LUTRON) | (DALI) |
| Beam Options | 180° Asymmetric (A) | | 360° Symmetric (S) |

Code Chart

| Range Name | Wattage | Beam Option | Height | Colour Temperat ure | Control Option |
|---------------|---------|----------------|--------|---------------------------|-------------------|
| APOLLO | 12 | А | 280 | 4 | DALI |

APOLLO-12A2804DALI