

## Electrical Parameters

Power: 40W  
Input Voltage: 220-240V 50/60Hz  
Power Factor: 0.95, Flicker Free  
IP Rating: Standard IP20  
Dimmable: DALI dimmable or Optional  
Certificates: CE, ROHS, SAA  
Standards: EN 55015:2006+A1:2007+A2:2009 /  
EN 61000-3-2:2006+A1:2009+A2:2009 /  
EN 61000-3-3:2008/EN 61547:2009  
Cyanosis Observation index <2.0  
Certified by Lighting Lab International with  
NATA accredited test report



## Photometric Parameters

CRI:  $\geq 90$  Ra  
Beam Angle: 120°  
Colour Temperatures: 4000k



High lumen is achieved by using  
HONGLI TRONIC 2835 LED



HONGLI TRONIC



## Lifetime

Lifetime (F50): 40,000 hrs  
Lumen maintenance (L70): 40,000hrs  
Min/Max operating Temp -20°C /+40°C

## General Information

Body Material: Aluminium frame & plate  
Product Colour: Black / White





Order Code	Alpha Code	Watt	Colour Temp.	Lumen Output	Product Colour
PEN-CYANOSIS-40W-4K-B-EL	CYPENDANT40W4K	40W	4000K	4900 lm	Black
PEN-CYANOSIS-40W-4K-W-EL					White

## Product Dimensions

