



Models: 100w, 150w, 200w

Surface mount LED canopy lights are suitable for both outdoor and indoor commercial applications such as loading docks, petrol stations, food processing plants and common areas.

Product Features

- Aluminium die cast housing
- Opal polycarbonate face
- Long operating life and performance
- 120° Beam Angle
- IP65 Waterproof housing
- Easy connect junction box on rear
- Replaceable Meanwell IP66 driver
- Optional mounting back plate to suit (Model: CL-MOUNT)



SPECIFICATION	ELG-CL-SM-100W-V	ELG-CL-SM-150W-V	ELG-CL-SM-200W-V
Colour Temperature	Cool White 5000K		
Lumen (lm)	8,882 lm	14,805 lm	18,217 lm
LED Efficiency (lm/w)	>140 lm/w		
Light Source	SMD LED's		
CRI (%)	>80%		
Beam Angle	120°		
Power Requirement	AC 100~240V		
Power Consumption	100w	150w	200w
Housing	Die Cast Aluminium and Opal PC Lens		
Lifespan	> 50,000 hours		
Operation Temperature	-20°C~+40°C		
Dimension (L x W x H)	455 x 455 x 110mm	580 x 580 x 120mm	
Weight	6kg	11.2kg	
Protection Rating	IP65		
Warranty	5 years		