



ELEVAGE
LIGHTING / GROUP

Consult. Supply. *Illuminate.*

**LED Panels
& Battens**

elevagegroup.com.au

PREMIUM BACKLIT UGR<19 PANEL

Product Features

Aluminium frame

PS diffuser

Backlit design

Steel body with PS prismatic lens

Flicker-free driver technology

Blue light hazard radiance: RG1

CRI >80

Beam Angle 90°

Available in 295x595, 595x595 & 1195x295cm



Electrical Parameters

Power Switchable – 25w, 30w, 35w, 40w

CCT changeable - 3000K, 4000K, 5000K

High output achieving >138lm/w

L90 >50,000hrs rated lifespan

Optional Triac, 1-10V or Dali dimming drivers



PREMIUM UGR<19 PANEL

Product Features

White Trim

120° Beam Angle

>81-101Lm/w efficacy

CRI >80 Ra

Aluminium with PS lens

Optional Triac or Dali/Push Dim

IP20



ELG WEATHERPROOF BATTEN

Product Features

Colour Temperature Options: 3000K
to 5500K

CRI: ≥ 80 Ra

Beam Angle: 120°

Lifetime (F50): 50,000 hours

Lumen maintenance (L70):
50,000hours

Min/Max operating Temp: -20°C
/+40°C



Electrical Parameters

Power: 20W - 40W

Input Voltage: 220-240V 50/60Hz Factor: 0.95,
Flicker Free

Stainless Steel Latches & Fixing Brackets Cable
Gland Entry: 20mm

IP Rating: IP65

IK Rating IK08

Certifications: CE, ROHS, SAA

Standards: EN 55015:2006+A1:2007+A2:2009 /

EN 61000-3-2:2006+A1:2009+A2:2009/

EN 61000-3-3:2008/EN 61547:2009



ELG INDOOR WIDE-BODY BATTEN

PRODUCT FEATURES

Wide body to cover existing installation marks

CCT changeable - 3000K, 4000K, 5000K

Dual power driver for multiple brightness options:

- ▶ 600mm/2ft - 10w/20w (1,200~2,400lm)
- ▶ 1200mm/4ft - 20w/40w (2,200~4,400lm)

2-Stage, flicker-free driver technology

Cold rolled, powder coated steel body

Aluminium LED module, polycarbonate diffuser

High light efficiency and low energy consumption

4ft Batten available in two widths

Optional:

- ▶ Emergency battery back-up
- ▶ Dimming - Triac, 1-10V, Dali



Consult. Supply. *Illuminate.*

Elevage Lighting Group
6/8 Murphy St, O'Connor
Perth WA, 6163

sales@elevagegroup.com.au