



Consult. Supply. <u>Illuminate</u>.

Solar Lighting

elephie



TRIC FLOODSOLAR SERIES

Product Features

Black frame Beam angle 120° >50,000 hrs lamp life IP65 rated Die Cast Aluminium Lithium Battery Solar Panel supplied



TRIC BOLLARD SOLAR 6 SERIES

Product Features

Size 900x360mm 10 – 12 hour duration per charge 4 hour charge time Die Cast Aluminium frame Operating temperature -15~+ 55° Life PO4 battery w/ 2yr Warranty Two 6V/4AH Batteries CRI >80 IP65 rated IK10 Rating







Consult. Supply. Illuminate.





LED RGBW SOLAR BOLLARD

Product Features

Complete solar bollard Easy to install, minimal maintenance RGB and white 120° Beam angle 900mm High Aluminium post with IK10 polycarbonate dome IP65 housing Automatic night-time operation, intelligent controller Supplied with remote control Replaceable battery pack 2 Year Warranty















LED SOLAR SENSOR STREET LIGHT

Product Features

Inbuilt PIR motion sensor Power Saving Mode (PSM) provides ~ 30% brightness until sensor detects movement Independently positioned solar panel Automatic night time operation Full powder coated aluminium housing Low battery dimming to prolong light MPPT controller – 15 ~ 20% more efficient Replaceable battery pack Customisable settings available IP65 weatherproof housing IK08 impact rating 2 year warranty







Consult.

Elevage Lighting Group has a design team with the purpose of enabling us to provide a complete service.

Our goal is to give you peace of mind knowing you meet all Australian Standards.

We are happy to provide designs for projects we are involved in along with our team's expertise from start to finish.

Our believe is that our job isn't finished until your job is complete, and we are a part of your team on your projects to ensure we can support a seamless transition to handover.





Consult. Supply. Illuninate.

Elevage Lighting Group 6/8 Murphy St, O'Connor Perth WA, 6163

sales@elevagegroup.com.au