

tric IK INGROUND Series



- 304SS+ Aluminium frame
- PG9 Cable gland, nickel-plated brass
- Voltage Range DC12V, DC24V
- Beam angle 10, 30, 45, 60, 90°
- Cable length to requirement
- >50,000 hrs lamp life
- Power factor >0.91
- CRI>70
- IP67 rated

Model	Power	Lumens	Colour Temp	Size (mm) W x H	Cutout (mm)	IK Rating
tric IK-INGROUND.3W3K	3w	300lm	3000k	115 x 90	80	IK08
tric IK-INGROUND.3W4K	3w	300lm	4000k	115 x 90	80	IK08
tric IK-INGROUND.3W6K	3w	300lm	6000k	115 x 90	80	IK08
tric IK-INGROUND.6W3K	6w	600lm	3000k	130 x 90	100	IK08
tric IK-INGROUND.6W4K	6w	600lm	4000k	130 x 90	100	IK08
tric IK-INGROUND.6W6K	6w	600lm	6000k	130 x 90	100	IK08
tric IK-INGROUND.14W3K	14w	1300lm	3000k	160 x 90	145	IK08
tric IK-INGROUND.14W4K	14w	1350lm	4000k	160 x 90	145	IK08
tric IK-INGROUND.14W6K	14w	1400lm	6000k	160 x 90	145	IK08

