

## tric PERISCOPE Series



- Aluminium White Frame
- CRI 90
- Bridgelux COB Chip
- SCDM>3
- Dimming Available - Triac  
- Dali
- Voltage Range AC100 – 240V
- Power factor >0.91
- IP20 rated
- >50,000 hrs lamp life
- Beam Angles Available  
12°, 24°, 40°



- Square Frame available in  
single and double luminaire  
fittings



## tric PERISCOPE Series

Model	Power	Lumens	Colour Temp	Cutout $\phi$ mm	Size mm D x H
tric PERISCOPE-12W3K.WH	12w	1125lm	3000k	95	105 x 127
tric PERISCOPE-12W4K.WH	12w	1150lm	4000k	95	105 x 127
tric PERISCOPE-12W5K.WH	12w	1175lm	5000k	95	105 x 127
tric PERISCOPE-12W6K.WH	12w	1200lm	6000k	95	105 x 127
tric PERISCOPE-12W3K.SQ.WH	12w	1125lm	3000k	95	112*112*127
tric PERISCOPE-12W4K.SQ.WH	12w	1150lm	4000k	95	112*112*127
tric PERISCOPE-12W5K.SQ.WH	12w	1175lm	5000k	95	112*112*127
tric PERISCOPE-12W6K.SQ.WH	12w	1200lm	6000k	95	112*112*127
tric PERISCOPE-30W3K.WH	30w	3300lm	3000k	125	135 x 145
tric PERISCOPE-30W4K.WH	30w	3375lm	4000k	125	135 x 145
tric PERISCOPE-30W5K.WH	30w	3425lm	5000k	125	135 x 145
tric PERISCOPE-30W6K.WH	30w	3500lm	6000k	125	135 x 145
tric PERISCOPE-30W3K.SQ.WH	30w	3300lm	3000k	125	137*137*145
tric PERISCOPE-30W4K.SQ.WH	30w	3375lm	4000k	125	137*137*145
tric PERISCOPE-30W5K.SQ.WH	30w	3425lm	5000k	125	137*137*145
tric PERISCOPE-30W6K.SQ.WH	30w	3500lm	6000k	125	137*137*145
tric PERISCOPE-24W3K.WH	2*12w	2250lm	3000k	195 x 100	210*112*127
tric PERISCOPE-24W4K.WH	2*12w	2300lm	4000k	195 x 100	210*112*127
tric PERISCOPE-24W5K.WH	2*12w	2350lm	5000k	195 x 100	210*112*127
tric PERISCOPE-24W6K.WH	2*12w	2400lm	6000k	195 x 100	210*112*127
tric PERISCOPE-24W3K.SQ.WH	2*12w	2250lm	3000k	195 x 100	210*112*127
tric PERISCOPE-24W4K.SQ.WH	2*12w	2300lm	4000k	195 x 100	210*112*127
tric PERISCOPE-24W5K.SQ.WH	2*12w	2350lm	5000k	195 x 100	210*112*127
tric PERISCOPE-24W6K.SQ.WH	2*12w	2400lm	6000k	195 x 100	210*112*127

- Add .DIM for Triac Dimming
- Add .DALI for Dali Dimming
  
- Example - tric PERISCOPE-30W4K.WH.DALI

