

trics LINEAR RING Series

eLEDtrics LINEAR RINGS were introduced to allow creativity in design. This product is a part of our Linear range. Sleek and stylish with flexibility to be surface mounted or installed as a single feature pendant and in groups to create amazing patterns.

- Beam angle 120°
- Voltage AC 200-240V
- UGR<19
- 3 Step MacAdam Ellipse
- >50,000 hrs lamp life
- Power factor >0.90
- IP20
- CRI >90

Available in black, white, and silver frame.

Colours and RGB available upon request.



tric LINEAR RING Series

Model	Power	Lumens	Colour Temp	Size (mm) Dia x W x H
tric LINEARRING-80W3K.BLK	80w	7900lm	3000k	1200x51x75
tric LINEARRING-80W4K.BLK	80w	8000lm	4000k	1200x51x75
tric LINEARRING-80W3K.SIL	80w	7900lm	3000k	1200x51x75
tric LINEARRING-80W4K.SIL	80w	8000lm	4000k	1200x51x75
tric LINEARRING-80W3K.WHT	80w	7900lm	3000k	1200x51x75
tric LINEARRING-80W4K.WHT	80w	8000lm	4000k	1200x51x75
tric LINEARRING-120W3K.BLK	120w	11000lm	3000k	1500x51x75
tric LINEARRING-120W4K.BLK	120w	12000lm	4000k	1500x51x75
tric LINEARRING-120W3K.SIL	120w	11000lm	3000k	1500x51x75
tric LINEARRING-120W4K.SIL	120w	12000lm	4000k	1500x51x75
tric LINEARRING-120W3K.WHT	120w	11000lm	3000k	1500x51x75
tric LINEARRING-120W4K.WHT	120w	12000lm	4000k	1500x51x75
tric LINEARRING-150W3K.BLK	150w	13500lm	3000k	2100x51x75
tric LINEARRING-150W4K.BLK	150w	15000lm	4000k	2100x51x75
tric LINEARRING-150W3K.SIL	150w	13500lm	3000k	2100x51x75
tric LINEARRING-150W4K.SIL	150w	15000lm	4000k	2100x51x75
tric LINEARRING-150W3K.WHT	150w	13500lm	3000k	2100x51x75
tric LINEARRING-150W4K.WHT	150w	15000lm	4000k	2100x51x75
tric LINEARRING-250W3K.BLK	250w	23000lm	3000k	3000x51x75
tric LINEARRING-250W4K.BLK	250w	25000lm	4000k	3000x51x75
tric LINEARRING-250W3K.SIL	250w	23000lm	3000k	3000x51x75
tric LINEARRING-250W4K.SIL	250w	25000lm	4000k	3000x51x75
tric LINEARRING-250W3K.WHT	250w	23000lm	3000k	3000x51x75
tric LINEARRING-250W4K.WHT	250w	25000lm	4000k	3000x51x75

