

## tronic LINEAR BATTEN Series



- Suspended or Surface Mounting
- Beam angles 120°
- Boke LED Driver
- Edison 2835 LED
- Voltage AC 100-277V
- Voltage DC 30-40V
- >50,000 hrs lamp life
- Power factor >0.92
- IP20
- CRI >80
- 3 Step MacAdam Ellipse
- Operating Temperature -25~+45°C



## tric LINEAR BATTEN Series

Model	Power	Lumens	Colour Temp	Size (mm) L x W x H
tric LINEARBATTEN-20W3K.600	20w	1800lm	3000k	600x50x70
tric LINEARBATTEN-20W4K.600	20w	2000lm	4000k	600x50x70
tric LINEARBATTEN-20W3K.600DIM	20w	1800lm	3000k	600x50x70
tric LINEARBATTEN-20W4K.600DIM	20w	2000lm	4000k	600x50x70
tric LINEARBATTEN-20W3K.600DALI	20w	1800lm	3000k	600x50x70
tric LINEARBATTEN-20W4K.600DALI	20w	2000lm	4000k	600x50x70
tric LINEARBATTEN-40W3K.1200	30w	2700lm	3000k	1200x50x70
tric LINEARBATTEN-40W4K.1200	30w	3000lm	4000k	1200x50x70
tric LINEARBATTEN-40W3K.1200DIM	30w	2700lm	3000k	1200x50x70
tric LINEARBATTEN-40W4K.1200DIM	30w	3000lm	4000k	1200x50x70
tric LINEARBATTEN-40W3K.1200DALI	30w	2700lm	3000k	1200x50x70
tric LINEARBATTEN-40W4K.1200DALI	30w	3000lm	4000k	1200x50x70
tric LINEARBATTEN-50W3K.1500	50w	4500lm	3000k	1500x50x70
tric LINEARBATTEN-50W4K.1500	50w	5000lm	4000k	1500x50x70
tric LINEARBATTEN-50W3K.1500	50w	4500lm	3000k	1500x50x70
tric LINEARBATTEN-50W4K.1500	50w	5000lm	4000k	1500x50x70
tric LINEARBATTEN-50W3K.1500	50w	4500lm	3000k	1500x50x70
tric LINEARBATTEN-50W4K.1500	50w	5000lm	4000k	1500x50x70

