

tronic LINEAR DUO Series



- Suspended Mounting
- Beam angles 110°
- Edison 2835 LED
- 3 Step MacAdam Ellipse
- Voltage AC 100-277 V
- >50,000 hrs lamp life
- Power factor >0.90
- IP20
- CRI >90
- Operating Temperature -25~+45°C
- Dali option available
- Flicker Free Boke LED Driver
- 5 year warranty



tric LINEAR DUO Series

Model	Downlight Watts	Uplight Watts	Downward Lumens	Uplight Lumens	Colour Temp	Size (mm) L x W x H
tric LINEARDUO-30W3K.600	20w	10w	1800lm	900lm	3000k	600x72x80
tric LINEARDUO-30W4K.600.	20w	10w	2000lm	1000lm	4000k	600x72x80
tric LINEARDUO-30W5K.600	20w	10w	2100lm	1050lm	5000k	600x72x80
tric LINEARDUO-30W6K.600	20w	10w	2200lm	1100lm	6000k	600x72x80
tric LINEARDUO-40W3K.900	27w	13w	2550lm	1250lm	3000k	900x72x80
tric LINEARDUO-40W4K.900	27w	13w	2600lm	1300lm	4000k	900x72x80
tric LINEARDUO-40W5K.900	27w	13w	2650lm	1350lm	5000k	900x72x80
tric LINEARDUO-40W6K.900	27w	13w	2700lm	1400lm	6000k	900x72x80
tric LINEARDUO-50W3K.1200	33w	17w	3250lm	1550lm	3000k	1200x72x80
tric LINEARDUO-50W4K.1200	33w	17w	3300lm	1600lm	4000k	1200x72x80
tric LINEARDUO-50W5K.1200	33w	17w	3350lm	1650lm	5000k	1200x72x80
tric LINEARDUO-50W6K.1200	33w	17w	3400lm	1700lm	6000k	1200x72x80
tric LINEARDUO-60W3K.1500	40w	20w	3800lm	1900lm	3000k	1500x72x80
tric LINEARDUO-60W4K.1500	40w	20w	3900lm	1950lm	4000k	1500x72x80
tric LINEARDUO-60W5K.1500	40w	20w	4000lm	2000lm	5000k	1500x72x80
tric LINEARDUO-60W6K.1500	40w	20w	4100lm	2050lm	6000k	1500x72x80
tric LINEARDUO-80W3K.1800	54w	26w	5150lm	2450lm	3000k	1800x72x80
tric LINEARDUO-80W4K.1800	54w	26w	5250lm	2550lm	4000k	1800x72x80
tric LINEARDUO-80W5K.1800	54w	26w	5350lm	2650lm	5000k	1800x72x80
tric LINEARDUO-80W6K.1800	54w	26w	5450lm	2750lm	6000k	1800x72x80

➤ Dimmable and Dali options available on request.

