

## tric LINEAR SLIM Series



- Suspended or Surface Mounting
- Beam angles 110°
- Boke LED External Driver
- Edison 2835 LED
- Voltage AC 100-277 V
- >50,000 hrs lamp life
- Power factor >0.90
- IP20
- CRI >90
- 3 Step MacAdam Ellipse
- Operating Temperature -25~+45°c



## tric LINEAR SLIM Series

Model	Power	Lumens	Colour Temp	Size (mm) L x W x H
tric LINEARSLIM-30W3K.1200DIM	30w	2900lm	3000k	1200x42x65
tric LINEARSLIM-30W4K.1200DIM	30w	2950lm	4000k	1200x42x65
tric LINEARSLIM-30W5K.1200DIM	30w	3000lm	5000k	1200x42x65
tric LINEARSLIM-30W6K.1200DIM	30w	3050lm	6000k	1200x42x65
tric LINEARSLIM-30W3K.1200DALI	30w	2900lm	3000k	1200x42x65
tric LINEARSLIM-30W4K.1200DALI	30w	2950lm	4000k	1200x42x65
tric LINEARSLIM-30W5K.1200DALI	30w	3000lm	5000k	1200x42x65
tric LINEARSLIM-30W6K.1200DALI	30w	3050lm	6000k	1200x42x65
tric LINEARSLIM-40W3K.1500DIM	40w	3850lm	3000k	1500x42x65
tric LINEARSLIM-40W4K.1500DIM	40w	3925lm	4000k	1500x42x65
tric LINEARSLIM-40W5K.1500DIM	40w	4000lm	5000k	1500x42x65
tric LINEARSLIM-40W6K.1500DIM	40w	4100lm	6000k	1500x42x65
tric LINEARSLIM-40W3K.1500DALI	40w	3850lm	3000k	1500x42x65
tric LINEARSLIM-40W4K.1500DALI	40w	3925lm	4000k	1500x42x65
tric LINEARSLIM-40W5K.1500DALI	40w	4000lm	5000k	1500x42x65
tric LINEARSLIM-40W6K.1500DALI	40w	4100lm	6000k	1500x42x65
tric LINEARSLIM-50W3K.1800DIM	50w	4900lm	3000k	1800x42x65
tric LINEARSLIM-50W4K.1800DIM	50w	5000lm	4000k	1800x42x65
tric LINEARSLIM-50W5K.1800DIM	50w	5100lm	5000k	1800x42x65
tric LINEARSLIM-50W6K.1800DIM	50w	5200lm	6000k	1800x42x65
tric LINEARSLIM-50W3K.1800DALI	50w	4900lm	3000k	1800x42x65
tric LINEARSLIM-50W4K.1800DALI	50w	5000lm	4000k	1800x42x65
tric LINEARSLIM-50W5K.1800DALI	50w	5100lm	5000k	1800x42x65
tric LINEARSLIM-50W6K.1800DALI	50w	5200lm	6000k	1800x42x65

\* Add BLK (Black) or WHT (White) to the end of the code to distinguish colour

