

Aallumio

HOTERU



DOWNLIGHT

a product data sheet by

Elevage Lighting Group



HOTERU SERIES

delivers a refined, modern design that enhances the visual appeal of any environment. Its contemporary lines focus light precisely while contributing to the overall aesthetics of the space.

a product data sheet by

Elevage Lighting Group

KEY FEATURES

- Aluminium frame
- CRI: > 90
- 3 Step MacAdam ellipse
- 100 lumens per watt
- Voltage range: AC200-240V
- Power factor: >0.90
- IP42 rated
- Beam angle: 15/24/38°
- Bridgelux Chip
- Lifud driver
- 50,000 hours lamp life





PRODUCT CONFIGURATION GUIDE

HOTERU SERIES range is available in the following structure and measurements to suit your project requirements.

Available Options

- Power: 6W, 10W, 15W (simplified on table for code purposes)
- Colour Temperature (CCT): 3000K, 4000K, 6000K (simplified on table for code purposes)



Image: HOTERU SERIES in black and white body colour to suit different project requirements.

STRUCTURE				MEASUREMENTS		
Power (Wattage)	CCT (K)	Control	Body Colour	Diameter (mm)	Height (mm)	Cutout (mm)
6	• 3 • 4 • 6	• Switching (S) • Dimming (DIM) • DALI	• Black (B) • White (W)	65	50	55
10				85	56	75
15				105	80	95

Ordering Code Structure

Based on the product configuration guide above, use the format below to create your code:

HOTERU

-

-

-

-

(Range Name)

(Power)

(CCT)

(Control)

(Body Colour)



a product data sheet by

Elevage Lighting Group