

eLEDtric

WP LINEAR



Details

Weatherproof Linear is built for performance and durability, delivering consistent, high-output illumination in all conditions. Ideal for architectural façades, pathways and landscape applications, it ensures reliability and precision across every outdoor project.

Key Features

- Aluminium die casting with glass
- OSRAM chip
- CRI 90
- Power factor: 0.95
- 100 Lumens per watt
- Beam Angle available: 30° or 60°
- SDCM 5
- Input voltage: AC200–240V
- Output voltage: DC24V
- IP65 Rated



Fremantle, WA



Moon & Mary Fremantle, WA

eLEDtric Across Australia

Our eLEDtric lighting solutions are installed across Australia, delivering reliable, high-performance illumination in diverse commercial environments. At Moon & Mary in Fremantle, the eLEDtric WP LINEAR provides precise architectural illumination, enhancing the venue's exterior and surrounding pathways with consistent, low-glare light.

Product Configuration Guide

The **tric WP LINEAR** range is available in the below structure and measurement options to suit different project requirements.

Available Options

- Power: 18W, 24W, 36W
- Colour Temperature (CCT): 3000K / 4000K (simplified on table for code purposes)

Structure				Measurements		
Power (Wattage)	CCT (K)	Body Colour	Control	Length (mm)	Width (mm)	Height (mm)
18W	• 3K • 4K	• Black (BLK) • Silver (SIL)	• Switch (S)	992	40	26
24W						
36W						

**Driver sold separately, allowing for a wider variety of control options*

Ordering Code Structure

Based on the product configuration guide above, use the format below to create your code:

tric WP LINEAR - - -
 (Range Name) (Power) (CCT) (Body Colour)

