

eLEDtric

PERISCOPE



Details

PERISCOPE downlight

is available in both single and double frame options, is perfect for galleries with its narrow beam angle that directs attention precisely where it's needed. Its focused lighting enhances artwork and displays, drawing viewers' eyes to key details and creating a compelling visual experience.



Key Features

- UGR < 22
- Bridgelux COB Chip
- Dimming Option Available
- Square Frame available in single and double luminaire fittings
- Aluminium White Frame
- CRI 95
- 100 Lumens per watt
- Beam Angles: 12°, 24°, 40°
- 3-Step MacAdam Ellipse
- Voltage Range: AC 100-240V
- Power Factor: >0.91
- IP20 Rated
- 50,000 Hours Lamp Life



Bundaberg
Central, QLD

eLEDtric Across Australia

Our eLEDtric lighting solutions are installed in projects across Australia, delivering reliable, high-performance illumination across a wide range of commercial environments. At Telstra Bundaberg Central, QLD, our lighting helps create a bright, modern and welcoming retail experience.



Telstra, Bundaberg Central

Product Configuration Guide

The **tric PERISCOPE** range is available in the following structure and measurements options to suit different project requirements.

Available Options

- Power: 12W, 30W, 2 x 12W (TWIN)
- Colour Temperature (CCT): 3000K, 4000K, 5000K, 6000K
- Control: Switch (S), Dimming (DIM), DALI
- Various Measurement

Structure			Measurements	
Power (Wattage)	CCT (K)	Control	Product Size (mm)	Cutout (mm)
12W	• 3K • 4K • 5K • 6K	• Switch (S) • Dimming (DIM) • DALI	Ø: 105 H: 127	Ø: 95
30W			Ø: 135 H: 145	Ø: 125
2x12W (TWIN)			L: 210 x W: 112 x H: 127	L: 195 x W: 100

Ordering Code Structure

Based on the product configuration guide above, use the format below to create your code:

tric PERISCOPE - - -

(Range Name) (Power) (CCT) (Control)

