

eLEDtric

STREET L



Details

STREET L lights are versatile fixtures designed for use in car parks and roadways, featuring adjustable angles to optimize light distribution. They can be mounted both vertically and horizontally, ensuring effective illumination in various settings.



Key Features

- IK08 rating
- 140 lumens per watt
- SDCM <3
- Integral 6KV surge protection
- Voltage: AC 100-277V
- THD <10%
- Power Factor: >0.92
- IP66 Rating
- CRI: >70
- Operating temperature -30°C to 45°C
- 65,000 hours lamp life
- 60mm SPIGOT (Standard), 76mm (available upon request)



 Canning Vale, WA



eLEDtric Across Australia

Our eLEDtric lighting solutions are installed at the Metcash Distribution Centre in Western Australia, delivering reliable, high-performance illumination throughout this large-scale industrial facility. Designed to enhance visibility, safety, and operational efficiency, our lighting provides dependable performance across warehouse, distribution, and logistics environments.

Product Configuration Guide

The **tric STREET L** range is available in the following structure and measurements options to suit different project requirements.

Available Options

- Power: 50W, 100W, 150W
- Colour Temperature (CCT): 3000K, 4000K, 5000K (simplified on table for code purposes)
- Control: Switch (S), Dimming (DIM) or DALI
- Various measurements and body colour

Structure				Measurements		
Power (Wattage)	CCT (K)	Control	Body Colour	Length (mm)	Width (mm)	Height (mm)
50W	• 3K • 4K • 5K • 6K	• Switch (S) • DALI	• Black (BLK) • White (WHT) • Silver (SIL)	198	88	528
100W				243	96	654
150W				298	96	709

Ordering Code Structure

Based on the product configuration guide above, use the format below to create your code:

tric STREET L - - - - -
 (Range Name) (Power) (CCT) (Control) (Body Colour)

