

LEDlux

SURFACE



DETAILS

COB SURFACE DOWNLIGHT features a chip-on-board design that delivers high-quality, focused illumination with adjustable colour temperature to suit any setting. Ideal for slab ceilings and those places a recessed downlight can't be installed, while creating an architectural feature, and layered ambiance.



Image: Available in premium White and Black finishes

KEY FEATURES

- External trailing edge dimmable led driver
- Triac-dimmable 5-100% dimming range, the heat dissipation fast, external trailing edge dimmable driver included,
- IP54 rated
- Flicker free
- Toughened glass diffuser
- CRI>90
- 90 lumens per watt
- Standard Beam Angle: 60°
- Voltage Range: AC 200-240V
- Heat sink: Die-cast aluminium
- 50,000 Hours Lamp Life

PRODUCT CONFIGURATION GUIDE

LUX COB SURFACE range is available in the below structure and measurement options to suit your project requirements.

Available Options

- Colour Temperature (CCT): Colour Switchable (CS): 3000K/ 4000K/ 6000K (simplified on table for code purposes)
- Body Colour: Black (BLK), White (WHT)

STRUCTURE			MEASUREMENTS	
Power (Wattage)	CCT (K)	Body Colour	Length (mm)	Height (mm)
15W	Colour Switchable (CS)	• Black (BLK) • White (WHT)	103	91

Ordering Code Structure

Based on the product configuration guide above, use the format below to create your code:

LUX-COB-SURFACE - 15W - CS - _____

(Range Name) (Power) (CCT) (Body Colour)

 LEDlux

