allumio

PIVOT



SURFACE MOUNTED

a product data sheet by

Elevage Lighting Group



PIVOT LIGHTING

is a versatile surface-mounted luminaire offering 360° rotation and 90° tilt for precise directional lighting. Its clean cylindrical form and flexible adjustment make it ideal for highlighting artwork, retail displays and architectural features within contemporary commercial spaces.

a product data sheet by

Elevage Lighting Group

KEY FEATURES

- Aluminium frame
- CRI: > 90
- 3 Step MacAdam ellipse
- 100 lumens per watt
- Voltage range: AC200-240V
- Power factor: >0.91
- IP40 rated
- COB LED
- Epistar Chips
- Beam angle: 24, 36°



PRODUCT CONFIGURATION GUIDE

PIVOT range is available in the following structure and measurements to suit your project requirements.

Available Options

- Power: 10W (simplified on table for code purposes)
- Colour Temperature (CCT): 3000K, 4000K, 5000K(simplified on table for code purposes)





STRUCTURE				MEASUREMENTS	
Power (Wattage)	**CCT** (K)	**Control**	Colour	**Length** (mm)	**Width** (mm)
10	• 3 • 4 • 5	• Switching (S) • Dimming (DIM) • DALI	• Black (B) • White (W)	185	60

Ordering Code Structure

Based on the product configuration guide above, use the format below to create your code:

PIVOT - **10** - ____ - ____ - ____

(Range Name) (Power) (CCT) (Control) (Colour)

3 year warranty

allumio

a product data sheet by

Elevage Lighting Group