allumio

RONDELLO



LINEAR

a product data sheet by

Elevage Lighting Group



RONDELLO Recessed Linear

Range combines luxury and versatility, perfect for highlighting ceilings or, thanks to its polarized filter, elegantly washing lower walls as a night light in corridors and hallways. Its refined design enhances any space while providing subtle illumination.

a product data sheet by

Elevage Lighting Group

KEY FEATURES

- CRI: > 90
- 4 Step MacAdam ellipse
- 90 lumens per watt
- Voltage range: AC200-240V
- Power factor: >0.90
- IP20 rated
- Beam angle: 30°
- Lifud Flicker free drivers
- Polarized filter
- Osram Chip
- Working temperature -20 ~ 50°C
- 50,000 hours lamp life



PRODUCT CONFIGURATION GUIDE

RONDELLO range is available in the following structure to suit your project requirements.

Available Options

- Power: 10W, 20W, 30W (simplified on table for code purposes)
- Colour Temperature (CCT): 3000K, 4000K, 5000K (simplified on table for code purposes)

STRUCTURE				MEASUREMENT		
Power (Wattage)	**CCT** (K)	**Control**	**Cutout** (mm)	**Length** (mm)	**Width** (mm)	**Height** (mm)
10	• 3 • 4 • 5	• Switch (S) • Dimming (Dim) • DALI	L139 X W40	146	45	50
20			L273 X W40	280	45	50
30			L406 X W40	413	45	50

Ordering Code Structure

Based on the product configuration guide above, use the format below to create your code:

RONDELLO - _____ - _____ - _____

(Range Name) (Power) (CCT) (Control)

3 year warranty

allumio

a product data sheet by

Elevage Lighting Group