eleDtric

STARLIGHT



ELEVAGE LIGHTING GROUP

eLEDtric

Details

STARLIGHT is a compact downlight designed to deliver focused illumination, ideal for highlighting artwork or architectural features. Its discreet form makes it the perfect feature fitting for creating subtle yet impactful moments within a space.

Key Features

- Bridgelux Chip
- Dimming Option Available
- CRI 90
- 90 Lumens per watt
- Standard Beam Angle: 38°
- 3-Step MacAdam Ellipse
- Voltage Range: AC 200-240V
- Power Factor: >0.90
- IP20 Rated
- 50,000 Hours Lamp Life

ELEVAGE LIGHTING GROUP

eLEDtric





Como Hotel, Como

eLEDtric Across Australia

Our eLEDtric lighting solutions are installed in projects across Australia, delivering reliable, high-performance illumination in a wide range of commercial environments. One of these projects is Como Hotel, Perth WA, where our lighting helps create a bright, welcoming dining experience.

ELEVAGE LIGHTING GROUP

Product Configuration Guide

The **tric STARLIGHT** range is available in the following structure and measurement options to suit different project requirements.

Available Options

- Colour Temperature (CCT): 3000K, 4000K, 5000K, 6000K (simplified on table for code purposes)
- Control: Switch (S) or Dimming (DIM)

Structure			Measurements		
Power (Wattage)	**CCT** (K)	**Control**	**Diameter** (mm)	**Height** (mm)	**Cutout** (mm)
5W	• 3K • 4K • 5K	• DALI • Dimming (DIM)	40	57	35

Ordering Code Structure

Based on the product configuration guide above, use the format below to create your code:

tric STAR - 5W - _____ - _____

(Range Name) (Power) (CCT) (Control)



ELEVAGE LIGHTING GROUP