LEADlux

COB DOWNLIGHT



ELEVAGE LIGHTING GROUP

LEADlux

DETAILS

COB DOWNLIGHT features a chip-on-board design that delivers high-quality, focused illumination with adjustable colour temperature to suit any setting. Its discreet gimbal mechanism allows for flexible directional lighting—ideal for highlighting artwork, architectural features, or creating layered ambiance.



Image: Available in White and Black finish

KEY FEATURES

- External trailing edge dimmable led driver
- Triac-dimmable 5-100% dimming range, the heat dissipation fast, external trailing edge dimmable driver included,
- IP44 rated
- Flicker free
- Toughened glass diffuser
- Flex and plug included
- Standard Beam Angle: 60°, tilt angle: 30°
- Voltage Range: AC 200-240V
- Heat sink: Polyamide and aluminium
- 50,000 Hours Lamp Life

ELEVAGE LIGHTING GROUP

PRODUCT CONFIGURATION GUIDE

LUX COB range is available in the below structure and measurement options to suit your project requirements.

Available Options

- Colour Temperature (CCT): Colour Switchable (CS): 3000K/ 4000K/ 6000K (simplified on table for code purposes)
- Body Colour: Black (BLK), White (WHT)

STRUCTURE			MEASUREMENTS		
Power (Wattage)	**CCT** (K)	**Body Colour**	**Diameter** (mm)	**Height** (mm)	**Cutout** (mm)
13W	Colour Switchable (CS)	• Black (BLK) • White (WHT)	102	77	90

Ordering Code Structure

Based on the product configuration guide above, use the format below to create your code:

LUX-COB - 13W - CS - _____

(Range Name) (Power) (CCT) (Body Colour)

ELEVAGE LIGHTING GROUP

5 year warranty


LEADlux
ELEVAGE
LIGHTING GROUP