STUDIO
LINEAR

web	elevagegroup.com.au
linkedin	Elevage Lighting Group
instagram/ facebook	elevagelighting



SURGE
by Elevage Lighting Group

SITE

High-performance RGBW linear luminaire designed for façade washing and outdoor architectural applications.



[figure 1]

KEY FEATURES

- Aluminium die cast housing
- Standard beam angle: 120°
- Voltage AC200-240V
- 90-120 Lumens per watt
- SMD3030 / 5050
- 50/60Hz
- Controlled by App (Bluetooth)
- IP66 Rated
- Temperature: -25°C to 50°C

SURGE
by Elevage Lighting Group

PRODUCT CONFIGURATION GUIDE

The Studio Linear is available in the below structure and measurement.

STRUCTURE			MEASUREMENTS		
Power (Wattage)	CCT (K)	Body Colour	Length (mm)	Width (mm)	Height (mm)
48W	RGBW	Black	410	65	40
72W			410	120	45
96W			410	120	45
120W			410	120	45
148W			410	120	45

ORDERING CODE STRUCTURE

Based on the product configuration guide above, the product code is

SURGE-STUDIO-LINEAR-_____

(Range Name) (Power)

3 year warranty

SURGE by Elevage Lighting Group

SURGE

by Elevage Lighting Group