WEATHERPROOF
LINEAR

web	elevagegroup.com.au
linkedin	Elevage Lighting Group
instagram/ facebook	elevagelighting



SURGE
by Elevage Lighting Group

SITE

High-performance RGBW weatherproof linear luminaire designed for façade washing and outdoor architectural applications.



[figure 1]

Claremont Quaters:
Façade Lighting
DMX Application

KEY FEATURES

- Aluminium alloy body
- Weatherproof
- Tempered glass diffuser
- IP65
- Epistar Chips
- Meanwell Driver, 1 driver powers 7 units
- CRI >80
- Beam angle 30°
- 100 lumens per watt
- Voltage 24V (200-240V)
- Power factor: >0.91
- Operating temperature -30~+45°C

SURGE
by Elevage Lighting Group

PRODUCT CONFIGURATION GUIDE

The Weatherproof Linear is available in the below structure and measurement.

STRUCTURE			MEASUREMENTS			
Power (Wattage)	CCT (K)	Body Colour	Length (mm)	Width (mm)	Height (mm)	Bracket Height (mm)
36W	RGBW	Silver	982	50	53	43

ORDERING CODE STRUCTURE

Based on the product configuration guide above, the product code is

SURGE-WP-LINEAR -36W

(Range Name) (Power)

3 year warranty

SURGE by Elevage Lighting Group

SURGE

by Elevage Lighting Group